

## BIDIM® GREEN NON-WOVEN GEOTEXTILE

## TECHNICAL DATA SHEET: CHARACTERISTIC VALUES

Bidim® Green is a premium non-woven geotextile made with Australian recycled plastics and designed to assist with a range of engineering problems including separation, filtration, cushioning and drainage in roads, rail, waste and containment, water and mining applications.

- · Made with a combination of recycled PET and virgin plastic material
- · Excellent filtration, separation, and cushioning properties
- · Strong three-dimensional structure with high elongation
- · Designed to meet the requirements of Australian & New Zealand road and rail authorities
- · Applicable for Road, Rail, Mining and Waste sectors









## **BIDIM GREEN - A14G - A49G CHARACTERISTIC VALUES TECHNICAL DATA**

QLD MRTS27   NSW TfNSW R63   NZ TNZ F/7						
GRADE	STRENGTH CLASS	GRAB TENSILE STRENGTH	TRAPEZOIDAL TEAR STRENGTH	G RATING	EOS - PORE SIZE - 0 <sub>95</sub>	FLOW RATE (Q <sub>100</sub> )
		N	N	-	μm	I/m²/s
		AS 3706.2	AS 3706.3	AUSTROADS 90	AS 3706.7	AS 3706.9
		Q VALUE	Q VALUE	Q VALUE	MEAN	MEAN
A14G	А	≥ 500	≥ 180	≥ 900	≤ 120	≥ 50
A19G	В	≥ 700	≥ 250	≥ 1350	≤ 120	≥ 50
A29G	С	≥ 900	≥ 350	≥ 2000	≤ 120	≥ 50
A39G	D	≥ 1200	≥ 450	≥ 3000	≤ 120	≥ 50
A49G	E	≥ 1600	≥ 650	≥ 4500	≤ 120	≥ 50

The data contained in this table is obtained from the manufacturer's laboratory testing. To ensure this information is current please contact your local branch of Geofabrics Australasia.

- 1. Permittivity / Q100 NSW and NZ ranges do not require characteristic Q values, however QLD Q value specification is met by all Bidim Green A range geotextile.
- 2. Characteristic value (Q) = Mean 0.83 x standard deviation of the lot tested.
- Bidim Green meets filtration classes I VIII for MRTS27 Geotextiles (Separation and Filtration). Bidim Green meets filtration classes 1-5 for TfNSW R63 QA Specifications - Geotextiles (Separation and Filtration). Bidim Green meets filtration classes 1-4 for TNZ F/7: Specifications - Geotextiles.





Visit geofabrics.co.nz or call 0800 60 60 20









